

SPECIFICATIONS



70" Extended Length		7019	7025	7034	7041	7050
Exterior Dimensions	length (in/mm)	70/1778	70/1778	70/1778	70/1778	70/1778
	width (in/mm)	48/1219	48/1219	48/1219	48/1219	48/1219
	height (in/mm)	19/483	25/635	34/864	41/1041	50/1270
Interior Dimensions	length (in/mm)	66.4/1687	66.4/1687	66.4/1687	66.4/1687	66.4/1687
	width (in/mm)	44.5/1130	44.5/1130	44.5/1130	44.5/1130	44.5/1130
	height (in/mm)	13.1/333	18.8/478	27.9/709	34.9/886	44/1118
	height to fill line (in/mm)	12.1/307	17.9/455	26.9/683	34/864	43/1092
Drop Door Options		N/A	0, 1 or 2	0, 1 or 2	0, 1 or 2	0, 1 or 2
Container Volume	ft ³ /m ³	20.7/0.58	30.6/0.86	46/1.29	58.1/1.63	73.5/2.058
Container Capacity	Rigid (lb/Kg)	2000/907	2000/907	2000/907	2000/907	2000/907
	Distributed (lb/Kg)	1500/680.4	1500/680.4	1500/680.4	1500/680.4	1500/680.4
	Wing Wall (lb/Kg)	N/A	N/A	1000/454	N/A	1000/454
Stack Height	Static/Dynamic	4/4	4/4	4/3	4/2	4/2
Tare Weight (may vary)	(lb/Kg)	142/64	173/78	228/103	267/121	303/137
Collapsed Height	(in/mm)	N/A	13.3/338	13.3/338	29.2/742	29.2/742
Return Ratio		1:1	1.9:1	2.6:1	1.4:1	1.7:1
Truckload Quantity (Collapsed)	48' with lid/no lid	64/80	96/128	96/128	48/48	48/48
	53' with lid/no lid	69/85	104/136	104/136	51/51	51/51
Truckload Quantity (Open)	48' with lid/no lid	64/80	48/64	32/48	32/32	16/32
	53' with lid/no lid	69/85	52/68	35/51	34/34	18/34
40' ISO Container (Collapsed)	Std. with lid/no lid	36/36	45/63	45/63	18/27	18/27
	Hi Cube with lid/no lid	36/45	54/72	54/72	27/27	27/27
Standard Color		Black	Black	Black	Black	Black

Rigid load: Part is rigid across length and spans a minimum of 54" (64.5" container) or 60" (70" container).
 Distributed load: All other unsupported loads.

All dimensions and specifications are approximate. Interior height dimensions measured from center; variances may result due to center crown. Tare weight is based on the 2 drop door black model and will vary based on color and configuration. Performance characteristics are based on uniform static loads and may be affected by concentrated loads and elevated temperatures.

Material: HDPE materials and workmanship guaranteed for 3 years.

(800) 945 - 8304

contact@reusablepkg.com