

SPECIFICATIONS



Fixed Wall		4512	4515	4517	4519	4521	4524
Exterior Dimensions	length (in/mm)	45/1143	45/1143	45/1143	45/1143	45/1143	45/1143
	width (in/mm)	48/1219	48/1219	48/1219	48/1219	48/1219	48/1219
	height (in/mm)	12.1/307	15/381	16.9/429	19.3/490	21.3/540	24.8/630
Interior Dimensions	length (in/mm)	41.5/1054	41.5/1054	41.5/1054	41.5/1054	41.5/1054	41.5/1054
	width (in/mm)	44.3/1125	44.3/1125	44.3/1125	44.3/1125	44.3/1125	44.3/1125
	height (in/mm)	6.4/163	9.3/236	11.3/287	13.7/348	15.7/399	19/483
	height to fill line (in/mm)	5.4/137	8.3/210	10.3/262	12.7/323	14.7/373	18/457
Container Volume	ft ³ /m ³	5.6/16	8.8/25	10.9/31	13.2/37	15.4/43	19.2/54
Container Capacity	(lb/Kg)	2000/907	2000/907	2000/907	2000/907	2000/907	2000/907
Stack Height	Static	6	6	6	6	6	6
	Dynamic	6	6	6	6	6	4
Tare Weight (may vary)	(lb/Kg)	76/34	86/39	100/45	102/46	108/49	120/54
Return Ratio		1:1	1:1	1:1	1:1	1:1	1:1
Truckload Quantity	48' w/lid no lid	168/216	144/168	120/144	120/120	96/120	96/96
	53' w/ lid/no lid	182/234	156/182	130/156	130/130	104/130	104/104
40' ISO Container	Std. w/lid no lid	126/144	90/108	90/90	72/90	72/72	54/54
	Hi Cube w/lid no lid	126/162	108/126	90/108	90/90	72/90	72/72
Standard Color		Black	Black	Black	Black	Black	Black

All dimensions and specifications are approximate. Interior height dimensions measured from center; variances may result due to center crown. Tare weight is based on the 2-drop door black model, and will vary based on color and configuration. Performance characteristics are based on uniform static loads and elevated temperatures.

Materials and workmanship guaranteed for 3 years. Material: HDPE

(800) 945 - 8304
contact@reusablepkg.com